

XPERT TENT 24 SQM



FLAME RETARDANT
CPAI-84 / 6



GOOD WIND
RESISTANCE



UV RESISTANT



DISINFECTABLE



EASY SETUP



ALL CLIMATES



DESCRIPTION

- » New generation of multipurpose tents
- » Removable groundsheet included.
- » Integrated / removable shade cover with mesh awnings.
- » With vertical walls, creating 25% more inner volume.
- » Enhanced ventilation thanks to large windows and gable ventilation openings.
- » Rot and mildew proof, easy to clean and disinfect.
- » Can be used for storage, hospital, dispensary, school, office

MAIN MATERIALS

OUTER TENT LINER	Woven black-out PE 250 gsm - water, rot and UV proof - FR CPAI-84 Section 6
SHADE COVER	Woven PE 175 gsm - water, rot and UV proof - FR CPAI-84 Section 6
FRAME	Aluminium pipes with steel cross pipe connectors
GROUND SHEET	Woven PE 250 gsm - FR CPAI-84 Section 5
WINDOWS	3 layered: roll-up PE flap, fixed mosquito mesh and transparent PVC roll-up flap
GUY ROPES AND RUNNERS	6 mm black fluorescent cords Metal spring or elastic shock absorber Red metal guy runner

UNICEF STANDARD
CUSTOMER REFERENCE

HPT - S5088024

XPERT TENT 24 SQM

DIMENSIONS

LENGTH x WIDTH OUTER TENT	400 x 600 cm
CENTRAL HEIGHT	300 cm
WALL HEIGHT	200 cm
SHADE COVER HEIGHT	330 cm
DOORS (H x W)	1 per gable 190 x 200 cm
WINDOWS	2 per side 135 x 135 cm
LENGTH x WIDTH OUTER TENT	400 x 600 cm

GRAPHIC REFERENCE



PERFORMANCE AND CHARACTERISTICS

SHELF LIFE	Min. 5 years
LIFE SPAN	Min. 18 months exposure in all climates, with proper anchoring and maintenance
FR	CPAI 84 Section 6 (max. afterflame avg 10s)
DESINFECTABILITY	Easily disinfected, not sensitive to fungi/mould
RESISTANCE WIND	Min. 100 km/h with shade net
SNOW LOAD	Min. 300 N/m with wire cable with tensioner
COLOR	Tent liner: white Groundsheet: grey

TENT FEATURES

TENT LINER PANELS	Separated roof, gables and wall panels for easy set up and handling.
DOOR	1 door opening per gable. Door flap can be opened and used as awning.
WINDOWS	2 windows on each side.
SHADE COVER	With anti-water pockets and integrated fuse systems for enhanced wind resistance and better roof load.
VENTILATION	Triangular gable top ventilation opening and side wall ventilation above each window.
AIR INLET	Ø 35 cm at left bottom side of each gable (inside view).
CHIMNEY PATCH	35 x 75 cm, made of non-perforated heat resistant material. Can be completely closed with roll down PE flap.
GROUNDSHEET	Bath-tub style with min. 15 cm upstanding sides with velcro-strip.
PEGS	4 T-Peg 50 cm, 6 T-Peg 40 cm, 10 Rebar Peg 60 cm, 4 earth anchors.

XPERT TENT 24 SQM

PACKING

PACKING UNIT (P.U.)	Packed into 2 strapped together wooden crates. Content of the boxes is packed into multiple PE carrying bags. Box 1: 225 x 69 x 35 c m - 142 kg Box 2: 225 x 69 x 30 cm - 125 kg
CONTENT P.U.	Tent liner, shade cover, groundsheet, frame, accessories, hammer and repair kit
P.U. MEASUREMENTS	DIMENSIONS: 225 x 69 x 74 cm WEIGHT: ± 267 VOLUME: 1,14 m ³
LOADING	PER 20 FT DC 24 pcs palletized PER 40 FT DC 48 pcs palletized PER 40 FT HC 48 pcs palletized
	<small>INDICATED WEIGHTS AND VOLUMES ARE FOR YOUR INFORMATION ONLY AND MAY VARY ACCORDING TO PRODUCT SPECIFICATION. FOR ALL DIMENSIONS AND WEIGHTS A TOLERANCE OF 3% IS APPLIED</small>

ADD-ONS

Connectability options: gable / lateral / cross connector
 Partition set
 Ceiling net
 Inner and winter liner: breathable FR fabric / breathable quilted FR fabric
 Cabins: individual cabin / isolation cabin / negative pressure cabin
 Sanitary solutions: toilet cabin / shower cabin
 Lighting kits
 Hard flooring
 A/C and heating solutions

Specifications & design may be altered without notice due to continuous product development.
 LAST UPDATED 6/2023

XPERT TENT 24 SQM

VISUAL REFERENCES

