

LOW THERMAL FLEECE BLANKET

PLT

ICRC/IFRC *standard*

> KNITTED BLANKET RAISED ON BOTH SIDES

WIDTH x LENGTH	150 x 200 cm ± 1%
WEIGHT	Min. 200 gsm

MATERIAL	MATERIAL	100% virgin polyester on dry weight as per ISO 1833
	TENSILE STRENGTH	Min. 200 N warp and weft as per ISO 13934-1
	TENSILE STRENGTH LOSS	Less than 5% after washing as per ISO 6330
	THICKNESS	Min. 3,5 mm as per ISO 5084 (IKPA on 2000 mm²)
	SHRINKAGE	Less than 5% after washing as per ISO 6330
	WEIGHT LOSS	Less than 5% after washing as per ISO 6330
	TOG	Min. 0,15 RCT (= 1,5 TOG)
	RESISTANCE TO AIRFLOW	Less than 500 L/m²/s as per ISO 9237 under 100 Pa pressure drop
	FINISH	Whipped seam of min.10 stitches per 10 cm
	ORGANOLEPTIC TEST	No bad smell, not irritating, no dust, PH between 4 and 9, fit for human use and free from VOC
	FLAME RESISTANCE	Flame proof as per ISO 12952-3&4
	CIGARETTE RESISTANCE	Cigarette proof as per ISO 12952-1&2
	COLOR	Grey shade blankets

PACKING	PACKING UNIT	Compressed bale
	PACKED QTY PER PACKING UNIT	20 pcs per bale
	DIMENSIONS WEIGHT VOLUME OF PACKING UNIT	80 x 53 x 47 cm 22 kg 0,2 m³
	PACKED QTY PER PALLET	Up to 8 bales per CRI pallet
	DIMENSIONS WEIGHT VOLUME OF PALLET	115 x 75 x 115 to 230 cm 101 or 190 kg 1 or 2 m³
	PACKED QTY PER 20FT DC CTN	2920 pcs unpalletised 2400 pcs palletised
	PACKED QTY PER 40FT DC CTN	6000 pcs unpalletised 4800 pcs palletised
	PACKED QTY PER 60FT DC CTN	7200 pcs unpalletised 4800 pcs palletised

INDICATED WEIGHTS AND VOLUMES ARE FOR YOUR INFORMATION ONLY AND MAY VARY ACCORDING TO PRODUCT SPECIFICATION TOLERANCES. PLEASE CONTACT US FOR THE EXACT INFORMATION.

MARKING	Label with washing instructions
STOCKS	Pakistan
PRODUCTION CAPACITY	80000 units per week*

Tel.: +32 (0) 55 23 17 54 | info@alpinter.com

*subject to confirmation

EUROPE BELGIUM | MIDDLE EAST DUBAI | EAST AFRICA UGANDA | ASIA HONG KONG

ALPINTER
www.alpinter.com

