

FLAME RETARDANT CPAI-84 / 6



FUNGI / MOLD RESISTANT



EASY SETUP



ALL CLIMATES



UV RESISTANT









UNHCR STANDARD

CUSTOMER REFERENCE

DESCRIPTION 00008038

» 5 person family tent with inner liner

» FR treated to CPAI-84 / 6 Standard

» Comfortable in all climates

MAIN MATERIALS

OUTER TENT Roof: approx. 380 gsm polyester-cotton - fire, water, rot and UV proof

Wall: approx. 250 gsm polyester-cotton - fire, water, rot and UV proof

INNER TENT

160 gsm polyester-cotton - fire & rotproof - cream color

GROUND SHEET

Sewn in bathtub ground sheet made of woven PE 180 gsm

MUD FLAP Woven PE - 180 GSM ICRC/IFRC standard

MOSQUITO NETTING Polyester PVC coated

POLES 1 ridge pipe 4 m | 2 upright poles 2,2 m | 6 side poles 1,25 cm | 4 door poles 1,4 m
PEGS 6 V pegs (25 x 25 x 3 mm) 35 cm | 4 candy cane pegs 30 cm | 26 o pegs 23 cm

COLOR Natural white / beige

DIMENSIONS

LENGTH x WIDTH OUTER TENT 660 x 400 cm FLOOR AREA 23 m²

CENTRAL HEIGHT 220 cm VESTIBULE 16m²

DOOR HEIGHT 140 cm LENGTH x WIDTH INNER TENT 395 x 380 cm

WALL HEIGHT 125 cm CENTRAL HEIGHT INNER TENT 210 cm WEIGHT 63 kg INNER SIDE WALL HEIGHT 115 cm



PERFORMANCE AND CHARACTERISTICS

SHELF LIFE Min. 3 years

TREATMENT Treated for fire, fungi & mold resistance

SETUP Easy setup (20 min | 3 persons)

TENT FEATURES

DOORS 2 doors outer tent (130 x 140 cm), 1 front and 1 back

2 doors inner tent (100 x 175 cm), 1 front and back

2 long side windows outer tent (360 x 60 cm), inner tent has two windows of equal

size

VENTILATION 2 ventilation openings, front and back

CHIMNEY 1 chimney reinforcement in in and outer tent

PACKING

WINDOWS

PACKING UNIT (P.U.) Tent in PE bag, with seperated webbing bands + handle

CONTENT P.U. Tent, inner tent with groundsheet, poles, accessories and hammer

QTY P.U. 1 piece

DIMENSIONS: 220 x 27 x 27 cm

P.U. MEASUREMENTS WEIGHT: 63 kg

VOLUME: 0,16 m³

QTY PALLET 15 pcs per metal stackable pallet

DIMENSIONS: 230 x 120 x 112,5 cm

PALLET MEASUREMENTS WEIGHT: 970 kg

VOLUME: 2,717 m³

PER 20 FT DC 170 pcs unpalletized | 150 pcs palletized

LOADING PER 40 FT DC 310 pcs unpalletized | 300 pcs palletized

PER 40 FT HC 350 to 380 pcs unpalletized | 300 pcs palletized

INDICATED WEIGHTS AND VOLUMES ARE FOR YOUR INFORMATION ONLY AND MAY VARY ACCORDING TO PRODUCT SPECIFICATION. FOR ALL DIMENSIONS AND WEIGHTS A TOLERANCE OF 3% IS APPLIED

ADD-ONS

Winterization kit

Shade net

Specifications & design may be altered without notice due to continuous product development. LAST UPDATED 6/2023



VISUAL REFERENCES









VISUAL REFERENCES







