

BLUE TENT

Basic Living Unit for Emergency

FAMILY TENTS

ICRC/IFRC/IOM standard



5 PERSON SELF-STANDING GEODESIC FAMILY TENT



- > EASY TO CARRY AND SET UP
- > RAPID DEPLOYMENT SHELTER

- > STABLE IN STRONG WINDS
- > COMFORTABLE IN ALL CLIMATES



PERFORMANCE	Minimum shelf life : 5 years	DIMENSIONS	LENGTH x WIDTH OUTER TENT	570 x 435 cm
	Slow flame spread		CENTRAL HEIGHT	250 cm
	Easily disinfected. Not sensitive to fungi/mould		DOOR HEIGHT	170 cm
	Easy setup (15 min / 3 person)		SHADE COVER SURFACE	20 m ²
	Wind resistance : up to 120 km/h			

MATERIALS	OUTER TENT	Woven PE – ICRC/IFRC standard	SHADE COVER	Woven PE – ICRC/IFRC standard
	GROUND SHEET	Woven PE – ICRC/IFRC standard	MOSQUITO NETTING	Polyester PVC COATED
	POLES	5 identical poles 834 cm (Aluminium 6061-T6 Ø 18,5 mm)		
	PEGS	6 T Pegs (25 x 25 x 3 mm) 40 cm		
	COLOR	White		

MAKE-UP	DOORS	2 doors (90 x 170 cm), 1 on the centre of each tent gable ends
	WINDOWS	6 windows (50 x 50 cm), 2 on each side of the tent and 1 next to each door
	VENTILATION	6 ventilation openings (85 x 55 cm) at the top of the tentroof above the doors
	CHIMNEY	1 chimney reinforcement

PACKING	PACKING UNIT	PE bag, with separated webbing bands + handle		
	CONTENT	Shade cover, outer tent, inner separation, accessories and hammer		
	PACKED QTY PER PACKING UNIT	1 piece	DIMENSIONS WEIGHT VOLUME OF PACKING UNIT	45 x 35 x 110 cm 46,5 kg 0,17 m ³
	PACKED QTY PER PALLET	6 pcs per pallet	DIMENSIONS WEIGHT VOLUME OF PALLET	115 x 106 x 113 cm 299 kg 1,38 m ³
	PACKED QTY PER 20FT DC CTN	160 pcs unpalletized 120 pcs palletized		
	PACKED QTY PER 40FT DC CTN	336 pcs unpalletized 264 pcs palletized		
	PACKED QTY PER 40FT HC CTN	388 pcs unpalletized 264 pcs palletized		
	MARKING	Upon customer request		

INDICATED WEIGHTS AND VOLUMES ARE FOR YOUR INFORMATION ONLY AND MAY VARY ACCORDING TO PRODUCT SPECIFICATION TOLERANCES. PLEASE CONTACT US FOR THE EXACT INFORMATION.

OPTIONS	Winterization kit, Inner tent	STOCKS	Belgium, Pakistan
---------	-------------------------------	--------	-------------------