# PLASTIC SHEETING 4X6 M



FUNGI / MOLD RESISTANT






DISINFECTABLE









### **IFRC/ICRC STANDARD**

CUSTOMER REFERENCE
HSHETARPW406

### » Reinforced flexible tarpaulins for temporary shelter or protection

» Made of woven HDPE black fibres

#### **MAIN MATERIALS**

**DESCRIPTION** 

MATERIAL Woven HDPE black fibers fabric laminated on both sides with LDPE coating

with 6 reinforced bands made of HDPE in the length

UV RESISTANCE Max. 20% loss on mechanical strength after 1500 UV exposure

TEMPERATURE RESISTANCE -20 to 80°C

TENSILE STRENGTH Min. 500 N and 15% to 25% elongation in warp and weft as per ISO 1421-1

Min. 700 N inside the reinforcements bands as per ISO 1421-1

TEARING STRENGTH Min. 100 N as per ISO 4674-1B

COLOR White with dark grey reinforcement bands I Inner black fibres to ensure opacity

# PLASTIC SHEETING 4X6 M

### **DIMENSIONS**

LENGTH x WIDTH 4 x 6 m

WEIGHT  $190 \text{ g/m}^2 \pm 20 \text{ g}$ , plus 10% for the reinforcement bands

### **PACKING**

PACKING UNIT (P.U.) Bale

QTY P.U. 5 pieces

DIMENSIONS: 76 x 57 x 13 cm

P.U. MEASUREMENTS WEIGHT: 23,25 kg

VOLUME: 0,054 m<sup>3</sup>

QTY PALLET 18 bales per CRI pallet

DIMENSIONS: 115 x 75 x 115 cm

PALLET MEASUREMENTS WEIGHT: 430 kg

VOLUME: 0,992 m<sup>3</sup>

PER 20 FT DC 2750 pcs unpalletized I 2700 pcs palletized LOADING PER 40 FT DC 5500 pcs unpalletized I 5130 pcs palletized

PER 40 FT HC 5500 pcs unpalletized I 5130 pcs palletized

INDICATED WEIGHTS AND VOLUMES ARE FOR YOUR INFORMATION ONLY AND MAY VARY ACCORDING TO PRODUCT SPECIFICATION. FOR ALLDIMENSIONS AND WEIGHTS A TOLERANCE OF 3% IS APPLIED

### **STOCKS**

Belgium, China, UAE