

PLASTIC SHEETING

4 X 5 M

PLASTIC SHEETING

UNHCR/UNICEF *standard*



› REINFORCED FLEXIBLE TARPAULINS FOR TEMPORARY SHELTER OR PROTECTION

WIDTH x LENGTH	4 x 5 m ± 1%
WEIGHT	190 g/m² ± 20 g (appr. 3,8 kg / unit)



FLAME RETARDANT / CPAI-84 Section 6

MATERIAL	MATERIAL	Woven HDPE black fibers fabric laminated on both sides with LDPE coating with aluminium eyelets on 4 sides every 100 cm
	UV RESISTANCE	Max. 5% loss on mechanical strength after 1500 UV exposure
	TEMPERATURE RESISTANCE	-20 to 80°C
	TENSILE STRENGTH	Min. 600 N in warp and weft (BS 2576, 50 mm grabtest or equivalent)
	TEARING STRENGTH	Min. 100 N in warp and weft as per ISO 4674
	COLOR	White on both sides Inner black fibers to ensure opacity

PACKING	PACKING UNIT	Bale
	PACKED QTY PER PACKING UNIT	5 pcs
	DIMENSIONS WEIGHT VOLUME OF PACKING UNIT	75 x 55 x 12 cm 19 kg 0,050 m³
	PACKED QTY PER PALLET	20 bales per CRI pallet
	DIMENSIONS WEIGHT VOLUME OF PALLET	115 x 75 x 115 cm 429 kg 0,992 m³
	PACKED QTY PER 20FT DC CTN	3000 pcs unpalletised 3000 pcs palletised
	PACKED QTY PER 40FT DC CTN	6000 pcs unpalletised 6000 pcs palletised
	PACKED QTY PER 40FT HC CTN	6300 pcs unpalletised 6000 pcs palletised

INDICATED WEIGHTS AND VOLUMES ARE FOR YOUR INFORMATION ONLY AND MAY VARY ACCORDING TO PRODUCT SPECIFICATION TOLERANCES. PLEASE CONTACT US FOR THE EXACT INFORMATION.

MARKING	Upon customer request
STOCKS	Belgium, Pakistan