

XPERT TENT - 72 SQM

MULTIPURPOSE TENTS



Specifications & design may be altered without notice due to continuous product development. LAST UPDATED 06/2020

UNICEF STANDARD
HIGH PERFORMANCE TENT 72 SQM

 **FLAME RETARDANT CPAI-84 / 6**

DESCRIPTION

- » New generation of multipurpose tents, available in different sizes.
- » With vertical walls, creating 25% more inner volume.
- » Resists wind over over 100 km/h.
- » With integrated / removable shade cover with mesh awnings.
- » Rot and mildew proof, easy to clean and disinfect.
- » Enhanced ventilation thanks to large windows and gable ventilation openings

DIMENSIONS

LENGTH x WIDTH OUTER TENT	1200 x 600 cm
CENTRAL HEIGHT	300 cm
WALL HEIGHT	200 cm
SHADE COVER HEIGHT	320 cm
DOORS	200 x 200 cm
WINDOWS	135 x 145 cm

MAIN MATERIALS

OUTER TENT LINER	Woven PE 250 gsm - ICRC/IFRC standard - FR CPAI-84 section 6
SHADE COVER	Woven PE 175 gsm - FR CPAI-84 section 6 - with mesh anti water pockets
FRAME	Aluminium pipes with steel cross pipe connectors
GROUND SHEET	Woven PE 250 gsm - FR CPAI-84 section 5
WINDOWS	3 layered: roll-up PE flap, fixed mosquito mesh and transparent PVC roll-up flap
GUY ROPES AND RUNNERS	6 mm black fluorescent cords Metal spring or elastic shock absorbers Red metal guy runner
PEGS	4 T-Peg 50 cm, 14 T-Peg 40 cm, 18 Rebar Peg 60 cm, 4 earth anchors

ALPINTER

+32 (0) 55 23 17 54 | info@alpinter.com | www.alpinter.com
HONG KONG ASIA | UGANDA EAST AFRICA | BELGIUM | BULGARIA | GERMANY EUROPE | UAE MIDDLE EAST

PERFORMANCE AND CHARACTERISTICS

SHELF LIFE	Min. 5 years
LIFE SPAN	Min. 18 months exposure in all climates, with proper anchoring and maintenance
FR	CPAI 84 Section 6 (max. afterflame avg 10s)
DESINFECTABILITY	Easily disinfected. Not sensitive to fungi/mould
WIND RESISTANCE	Min. 100 km/h with shade net
SNOW LOAD	Minimum 250 N/m ² with stability steel ropes.
COLORS	Tent liner: white Groundsheet: light grey

TENT AND FEATURES

TENT LINER PANELS	Separated roof, gables and wall panels for easy set up and handling
DOORS	1 door opening per gable. Door flap can be opened and used as awning.
WINDOWS	6 windows on each side.
CHIMNEY PATCH	35 x 75 cm, made of non-perforated heat resistant material. Can be completely closed with roll down PE flap
GROUND SHEET	Bath-tub style with min. 15 cm upstanding sides with velcro-strip.

PACKING

PACKING UNIT	Packed into 4 strapped together wooden crates. Content of the boxes is packed into multiple PE carrying bags. Box 1: 225 x 87 x 28 cm - 109 kg Box 2: 225 x 87 x 26 cm - 131 kg Box 3: 225 x 87 x 22 cm - 140 kg Box 3: 225 x 87 x 27 cm - 147 kg
CONTENT	Tent liner, shade cover, groundsheet, frame, accessories, hammer and repair kit
DIMENSIONS WEIGHT VOLUME	225 x 87 x 112 cm (incl. blocks) 529 kg 2,19 m ³
PACKED QTY 20 FT	12 pcs
PACKED QTY 40 FT	26 pcs
PACKED QTY 40 FT HC	26 pcs

INDICATED WEIGHTS AND VOLUMES ARE FOR YOUR INFORMATION ONLY AND MAY VARY ACCORDING TO PRODUCT SPECIFICATION. FOR ALL DIMENSIONS AND WEIGHTS A TOLERANCE OF 3% IS APPLIED

ADD-ONS

- Connectability options (gable / lateral / cross connector)
- Partition set
- Ceiling net
- Inner and winter liner: breathable FR fabric / breathable quilted FR fabric
- Cabins: individual cabin / isolation cabins / negative pressure cabins
- Sanitary solutions: toilet cabin / shower cabin
- Lighting kits
- Hard flooring

Specifications & design may be altered without notice due to continuous product development. LAST UPDATED 06/2020