

# XPERT TENT 48 SQM



FLAME RETARDANT  
CPAI-84 / 6



GOOD WIND  
RESISTANCE



UV RESISTANT



DISINFECTABLE



EASY SETUP



ALL CLIMATES



## DESCRIPTION

- » New generation of multipurpose tents
- » Removable groundsheet included.
- » Integrated / removable shade cover with mesh awnings.
- » With vertical walls, creating 25% more inner volume.
- » Enhanced ventilation thanks to large windows and gable ventilation openings.
- » Rot and mildew proof, easy to clean and disinfect.
- » Can be used for storage, hospital, dispensary, school, office , ...

## MAIN MATERIALS

OUTER TENT LINER	Woven black-out PE 250 gsm - water, rot and UV proof - FR CPAI-84 Section 6
SHADE COVER	Woven PE 175 gsm - water, rot and UV proof - FR CPAI-84 Section 6
PARTITION SET	Woven black-out PE 250 gsm - water, rot and UV proof - FR CPAI-84 Section 6
FRAME	Aluminium pipes with steel cross pipe connectors
GROUND SHEET	Woven PE 250 gsm - FR CPAI-84 Section 5
WINDOWS	3 layered: roll-up PE flap, fixed mosquito mesh and transparent PVC roll-up flap
GUY ROPES AND RUNNERS	6 mm black fluorescent cords   Metal spring or elastic shock absorbers   Red metal guy runner

**UNICEF STANDARD**  
**CUSTOMER REFERENCE**  
HPT - S5088048

# XPERT TENT 48 SQM

## DIMENSIONS

---

LENGTH x WIDTH OUTER TENT	800 x 600 cm
CENTRAL HEIGHT	300 cm
WALL HEIGHT	200 cm
SHADE COVER HEIGHT	330 cm
DOORS (H x W)	(H x W) 1 per gable   190 x 200 cm
WINDOWS	4 per side   135 x 135 cm

## PERFORMANCE AND CHARACTERISTICS

---

SHELF LIFE	Min. 5 years
LIFE SPAN	Min. 18 months exposure in all climates, with proper anchoring and maintenance
FR	CPAI 84 Section 6 (max. afterflame avg 10s)
DESINFECTABILITY	Easily disinfected, not sensitive to fungi/mould
RESISTANCE WIND	Min. 100 km/h with shade net
SNOW LOAD	Min. 300 N/m <sup>2</sup> with wire cable with tensioner
COLOR	Tent liner: white Groundsheet: grey

## TENT FEATURES

---

TENT LINER PANELS	Separated roof, gables and wall panels for easy set up and handling.
DOOR	1 door opening per gable. Door flap can be opened and used as awning.
WINDOWS	2 windows on each side.
SHADE COVER	With anti-water pockets and integrated fuse systems for enhanced wind resistance and better roof load.
PARTITION SET	Standard included, 600 x 200 cm
VENTILATION	Triangular gable top ventilation opening and side wall ventilation above each window.
AIR INLET	Ø 35 cm at left bottom side of each gable (inside view).
CHIMNEY PATCH	35 x 75 cm, made of non-perforated heat resistant material. Can be completely closed with roll down PE flap.
GROUNDSHEET	Bath-tub style with min. 15 cm upstanding sides with velcro-strip.
PEGS	4 T-Peg 50 cm, 10 T-Peg 40 cm, 14 Rebar Peg 60 cm, 4 earth anchors.

# XPERT TENT 48 SQM

## PACKING

	Packed into 3 strapped together wooden crates. Content of the boxes is packed into multiple PE carrying bags.
PACKING UNIT (P.U.)	Box 1: 225 x 69 x 34 cm - 133 kg Box 2: 225 x 69 x 34 cm - 137 kg Box 3: 225 x 69 x 34 cm - 129 kg
CONTENT P.U.	Tent liner, shade cover, groundsheet, frame, accessories, hammer and repair kit
P.U. MEASUREMENTS	DIMENSIONS: 225 x 69 x 112 cm (incl. blocks) WEIGHT: ± 399 kg VOLUME: 1,74 m <sup>3</sup>
LOADING	PER 20 FT DC 16 pcs palletized PER 40 FT DC 32 pcs palletized PER 40 FT HC 32 pcs palletized

INDICATED WEIGHTS AND VOLUMES ARE FOR YOUR INFORMATION ONLY AND MAY VARY ACCORDING TO PRODUCT SPECIFICATION.  
FOR ALL DIMENSIONS AND WEIGHTS A TOLERANCE OF 3% IS APPLIED

## ADD-ONS

Connectability options (gable / lateral / cross connector)	Sanitary solutions: toilet cabin / shower cabin
Partition set (standard included)	Lighting kits
Ceiling net	Hard flooring
Inner and winter liner: breathable FR fabric / breathable ` quilted FR fabric.	A/C and heating solutions
Cabins: individual cabin / isolation cabins / negative pressure cabins	Sanitary solutions: toilet cabin / shower cabin



# XPERT TENT 48 SQM

## VISUAL REFERENCES

