

XPERT TENT 48 SQM

MULTIPURPOSE TENTS



Specifications & design may be altered without notice due to continuous product development. LAST UPDATED 12/2020



UNICEF STANDARD

CUSTOMER REFERENCE

HPT - S5088048

DESCRIPTION

- » New generation of multipurpose tents
- » Removable groundsheet included.
- » Integrated / removable shade cover with mesh awnings.
- » With vertical walls, creating 25% more inner volume.
- » Enhanced ventilation thanks to large windows and gable ventilation openings.
- » Rot and mildew proof, easy to clean and disinfect.
- » Can be used for storage, hospital, dispensary, school, office , ...

DIMENSIONS

LENGTH x WIDTH OUTER TENT	800 x 600 cm
CENTRAL HEIGHT	300 cm
WALL HEIGHT	200 cm
SHADE COVER HEIGHT	330 cm
DOORS (H x W)	1 per gable 190 x 200 cm
WINDOWS	4 per side 135 x 135 cm

MAIN MATERIALS

OUTER TENT LINER	Woven black-out PE 250 gsm - water, rot and UV proof - FR CPAI-84 Section 6
SHADE COVER	Woven PE 175 gsm - water, rot and UV proof - FR CPAI-84 Section 6
FRAME	Aluminium pipes with steel cross pipe connectors
GROUND SHEET	Woven PE 250 gsm - FR CPAI-84 Section 5
WINDOWS	3 layered: roll-up PE flap, fixed mosquito mesh and transparent PVC roll-up flap
GUY ROPES AND RUNNERS	6 mm black fluorescent cords Metal spring or elastic shock absorbers Red metal guy runner

ALPINTER

+32 (0) 55 23 17 54 | info@alpinter.com | www.alpinter.com
HONG KONG **ASIA** | UGANDA **EAST AFRICA** | BELGIUM | BULGARIA | GERMANY **EUROPE** | UAE **MIDDLE EAST**

PERFORMANCE AND CHARACTERISTICS

SHELF LIFE	Min. 5 years
LIFE SPAN	Min. 18 months exposure in all climates, with proper anchoring and maintenance
FR	CPAI 84 Section 6 (max. afterflame avg 10s)
DESINFECTABILITY	Easily disinfected, not sensitive to fungi/mould
WIND RESISTANCE	Min. 100 km/h with shade net
SNOW LOAD	Min. 300 N/m ² with wire cable with tensioner
COLORS	Tent liner: white Groundsheet: grey

TENT FEATURES

TENT LINER PANELS	Separated roof, gables and wall panels for easy set up and handling.
DOORS	1 door opening per gable. Door flap can be opened and used as awning.
WINDOWS	2 windows on each side.
SHADE COVER	With anti-water pockets and integrated fuse systems for enhanced wind resistance and better roof load.
VENTILATION	Triangular gable top ventilation opening and side wall ventilation above each window.
AIR INLET	Ø 35 cm at left bottom side of each gable (inside view).
CHIMNEY PATCH	35 x 75 cm, made of non-perforated heat resistant material. Can be completely closed with roll down PE flap.
GROUNDSHEET	Bath-tub style with min. 15 cm upstanding sides with velcro-strip.
PEGS	4 T-Peg 50 cm, 10 T-Peg 40 cm, 14 Rebar Peg 60 cm, 4 earth anchors.
LOGO PRINTING	Available on shade-cover and gable flags

PACKING

PACKING UNIT	Packed into 3 strapped together wooden crates. Content of the boxes is packed into multiple PE carrying bags. Box 1: 225 x 69 x 34 cm - 125 kg Box 2: 225 x 69 x 34 cm - 136 kg Box 3: 225 x 69 x 34 cm - 133 kg
CONTENT	Tent liner, shade cover, groundsheet, frame, accessories, hammer and repair kit
DIMENSIONS WEIGHT VOLUME	225 x 69 x 112 cm (incl. blocks) 397 kg 1,74 m ³
PACKED QTY 20 FT	16 pcs
PACKED QTY 40 FT	32 pcs
PACKED QTY 40 FT HC	32 pcs

INDICATED WEIGHTS AND VOLUMES ARE FOR YOUR INFORMATION ONLY AND MAY VARY ACCORDING TO PRODUCT SPECIFICATION.

ADD-ONS

Connectability options (gable / lateral / cross connector)	Sanitary solutions: toilet cabin / shower cabin
Partition set	Lighting kits
Ceiling net	Hard flooring
Inner and winter liner: breathable FR fabric / breathable quilted FR fabric	A/C and heating solutions
Cabins: individual cabin / isolation cabins / negative pressure	