

# XPERT TENT 72 SQM

MULTIPURPOSE TENTS



Specifications & design may be altered without notice due to continuous product development. LAST UPDATED 11/2021



FLAME RETARDANT  
CPAI-84 / 6



GOOD WIND  
RESISTANCE



UV RESISTANT



DISINFECTABLE



EASY SETUP



ALL CLIMATES

## UNICEF STANDARD

CUSTOMER REFERENCE

HPT - S5088072

## DESCRIPTION

- » New generation of multipurpose tents
- » Removable groundsheet included.
- » Integrated / removable shade cover with mesh awnings.
- » With vertical walls, creating 25% more inner volume.
- » Enhanced ventilation thanks to large windows and gable ventilation openings.
- » Rot and mildew proof, easy to clean and disinfect.
- » Can be used for storage, hospital, dispensary, school, office, ...

## DIMENSIONS

LENGTH x WIDTH OUTER TENT	1200 x 600 cm
CENTRAL HEIGHT	300 cm
WALL HEIGHT	200 cm
SHADE COVER HEIGHT	330 cm
DOORS (H x W)	1 per gable   200 x 190 cm
WINDOWS	6 per side   135 x 135 cm

## MAIN MATERIALS

OUTER TENT LINER	Woven black-out PE 250 gsm - water, rot and UV proof - FR CPAI-84 Section 6
SHADE COVER	Woven PE 175 gsm - water, rot and UV proof - FR CPAI-84 Section 6
FRAME	Aluminium pipes with steel cross pipe connectors
GROUND SHEET	Woven PE 250 gsm - FR CPAI-84 Section 5
WINDOWS	3 layered: roll-up PE flap, fixed mosquito mesh and transparent PVC roll-up flap
GUY ROPES AND RUNNERS	6 mm black fluorescent cords   Metal spring or elastic shock absorbers   Red metal guy runner

ALPINTER

+32 (0) 55 23 17 54 | [info@alpinter.com](mailto:info@alpinter.com) | [www.alpinter.com](http://www.alpinter.com)  
HONG KONG ASIA | UGANDA EAST AFRICA | BELGIUM | BULGARIA | GERMANY EUROPE | UAE MIDDLE EAST

## PERFORMANCE AND CHARACTERISTICS

SHELF LIFE	Min. 5 years
LIFE SPAN	Min. 18 months exposure in all climates, with proper anchoring and maintenance
FR	CPAI 84 Section 6 (max. afterflame avg 10s)
DESINFECTABILITY	Easily disinfected, not sensitive to fungi/mould
WIND RESISTANCE	Min. 100 km/h with shade net
SNOW LOAD	Min. 300 N/m <sup>2</sup> with wire cable with tensioner
COLORS	Tent liner: white Groundsheet: grey

## TENT FEATURES

TENT LINER PANELS	Separated roof, gables and wall panels for easy set up and handling.
DOORS	1 door opening per gable. Door flap can be opened and used as awning.
WINDOWS	2 windows on each side.
SHADE COVER	With anti-water pockets and integrated fuse systems for enhanced wind resistance and better roof load.
VENTILATION	Triangular gable top ventilation opening and side wall ventilation above each window.
AIR INLET	Ø 35 cm at left bottom side of each gable (inside view).
CHIMNEY PATCH	35 x 75 cm, made of non-perforated heat resistant material. Can be completely closed with roll down PE flap.
GROUNDSHEET	Bath-tub style with min. 15 cm upstanding sides with velcro-strip.
PEGS	4 T-Peg 50 cm, 14 T-Peg 40 cm, 18 Rebar Peg 60 cm, 4 earth anchors.

## PACKING

PACKING UNIT	Packed into 4 strapped together wooden crates. Content of the boxes is packed into multiple PE carrying bags. Box 1: 225 x 87 x 28 cm - 116 kg (2 carry bags) Box 2: 225 x 87 x 26 cm - 139 kg (3 carry bags) Box 3: 225 x 87 x 22 cm - 139 kg (3 carry bags) Box 4: 225 x 87 x 27 cm - 141 kg (3 carry bags)
CONTENT	Tent liner, shade cover, groundsheet, frame, accessories, hammer and repair kit
DIMENSIONS   WEIGHT   VOLUME	225 x 87 x 112 cm (incl. blocks)   535 kg   2,19 m <sup>3</sup> (+- 1 %)
PACKED QTY 20 FT	12 pcs
PACKED QTY 40 FT	26 pcs
PACKED QTY 40 FT HC	26 pcs

## ADD-ONS

Connectability options (gable / lateral / cross connector)	Lighting kits
Partition set	Hard flooring
Ceiling net	Sanitary solutions: toilet cabin / shower cabin
Inner and winter liner: breathable FR fabric / breathable quilted FR fabric	Lighting kits Hard flooring
Cabins: individual cabin / isolation cabins / negative pressure cabins	A/C and heating solutions
Sanitary solutions: toilet cabin / shower cabin	