

PLASTIC SHEETING 4 X 5 M

PLASTIC SHEETING



Specifications & design may be altered without notice due to continuous product development. LAST UPDATED 11/2020

-  FLAME RETARDANT
CPAI-84 / 6
-  FUNGI / MOLD
RESISTANT
-  DISINFECTABLE
-  GOOD UV
RESISTANCE

UNHCR/UNICEF STANDARD

CUSTOMER REFERENCE

02617
S5086014

DESCRIPTION

- » Reinforced flexible tarpaulins for temporary shelter or protection
- » Made of woven HDPE black fibres

DIMENSIONS

LENGTH x WIDTH	4 x 5 m ± 1%
WEIGHT	190 g/m ² ± 20 g (approx. 3,8 kg / unit)

MAIN MATERIALS

MATERIAL	Woven HDPE black fibers fabric laminated on both sides with LDPE coating with aluminium eyelets on 4 sides every 100 cm
UV RESISTANCE	Max. 5% loss on mechanical strength after 1500 UV exposure
TEMPERATURE RESISTANCE	-20 to 80°C
TENSILE STRENGTH	Min. 600 N in warp and weft (BS 2576, 50 mm grabtest or equivalent)
TEARING STRENGTH	Min. 100 N in warp and weft as per ISO 4674
COLOR	White on both sides Inner black fibres to ensure opacity
LOGO PRINTING	Upon customer request

PACKING

PACKING UNIT	Bale
PACKED QTY PER PACKING UNIT	5 pcs
DIMENSIONS WEIGHT VOLUME	75 x 55 x 12 cm 19 kg 0,050 m ³
PACKED QTY PER PALLET	20 bales per CRI pallet
DIMENSIONS WEIGHT VOLUME	115 x 75 x 115 cm 429 kg 0,992 m ³
PACKED QTY PER 20 FT DC	3000 pcs unpalletized 3000 pcs palletized
PACKED QTY PER 40 FT DC	6000 pcs unpalletized 6000 pcs palletized
PACKED QTY PER 40 FT HC	6300 pcs unpalletized 6000 pcs palletized

INDICATED WEIGHTS AND VOLUMES ARE FOR YOUR INFORMATION ONLY AND MAY VARY ACCORDING TO PRODUCT SPECIFICATION TOLERANCES. PLEASE CONTACT US FOR THE EXACT INFORMATION.

STOCKS

Pakistan