

LOW THERMAL FLEECE BLANKET

BLANKETS



DESCRIPTION

- » Knitted blanket dry raised on both sides
- » 1 fold fleece layer in 100% virgin polyester
- » Min. 200 gsm - max. 400 gsm

ICRC/IFRC STANDARD

CUSTOMER REFERENCE

HSHEBLANPLT1

DIMENSIONS

LENGTH x WIDTH 150 x 200 cm ± 1%
WEIGHT Min. 200 gsm

MAIN MATERIALS

MATERIAL	100% virgin polyester on dry weight as per ISO 1833
TENSILE STRENGTH	Min. 200 N warp and weft as per ISO 13934-1
TENSILE STRENGTH LOSS	Less than 5% after washing as per ISO 6330
THICKNESS	Min 3,5mm as per ISO 5084 (IKPA on 2000 mm ²)
SHRINKAGE	Less than 5% after washing as per ISO 6330
WEIGHT LOSS	Less than 5% after washing as per ISO 6330
TOG	Min. 0,15 RCT (= 1,5 TOG)
RESISTANCE TO AIRFLOW	Less than 500 L/m ² /s as per ISO 9237 under 100 Pa pressure drop
FINISH	Whipped seam of min. 10 stitches per 10 cm
ORGANOLEPTIC TEST	No bad smell, not irritating, no dust, PH between 4 and 9, fit for human use and free from harmful VOC
FLAME RESISTANCE	Flame proof as per ISO 12952-3&4
CIGARETTE RESISTANCE	Cigarette proof as per ISO 12952-1&2
COLOR	Grey shade blanket

PACKING

PACKING UNIT	Compressed bale
PACKED QTY PER PACKING UNIT	20 pcs per bale
DIMENSIONS WEIGHT VOLUME	80 x 53 x 47 cm 22 kg 0,2 m ³
PACKED QTY PER PALLET	Up to 8 bales per CRI pallet
DIMENSIONS WEIGHT VOLUME	115 x 75 x 115 to 230 cm 101 or 190 kg 1 or 2 m ³
PACKED QTY PER 20 FT DC	2920 pcs unpalletized 2400 pcs palletized
PACKED QTY PER 40 FT DC	6000 pcs unpalletized 4800 pcs palletized
PACKED QTY PER 40 FT HC	7200 pcs unpalletized 4800 pcs palletized

INDICATED WEIGHTS AND VOLUMES ARE FOR YOUR INFORMATION ONLY AND MAY VARY ACCORDING TO PRODUCT SPECIFICATION TOLERANCES. PLEASE CONTACT US FOR THE EXACT INFORMATION.

STOCKS

Pakistan

ALPINTER

+32 (0) 55 23 17 54 | info@alpinter.com | www.alpinter.com
HONG KONG ASIA | UGANDA EAST AFRICA | BELGIUM | BULGARIA | GERMANY EUROPE | UAE MIDDLE EAST

Specifications & design may be altered without notice due to continuous product development. LAST UPDATED 11/2020