

BASE TENT 27,5 SQM



FUNGI / MOLD
RESISTANT



UV RESISTANT



ALL CLIMATES



**MSF/ICRC/IFRC STANDARD
MULTIPURPOSE TENT**

DESCRIPTION

- » Multipurpose tent, can be used for storage, hospital, dispensary, school, office, ...
- » With bathtub groundsheet included
- » Tents can be connected one to another to make a longer structure
- » Various options available (inner tent, partitions sets,...)

MAIN MATERIALS

OUTER TENT LINER	Roof: 440 gsm polyester cotton - water, rot and UV proof Wall: 320 gsm polyester cotton - water, rot and UV proof
MUD FLAP	550 gsm polyester with PVC coating on both sides - water, rot and UV proof
GROUND SHEET	550 gsm polyester with PVC coating on both sides - water, rot and UV proof
FRAME	Galvanized steel pipe Ø 30 x 1,5 mm

DIMENSIONS

LENGTH x WIDTH OUTER TENT	500 x 500 cm
FLOOR SURFACE	27,5 sqm
CENTRAL HEIGHT	250 cm
WALL HEIGHT	180 cm

BASE TENT 27,5 SQM

PERFORMANCE AND CHARACTERISTICS

SHELF LIFE	Min. 3 years
LIFE SPAN	Min. 12 months exposure in all climates, with proper anchoring and maintenance
TREATMENT	Fungi/mould resistant treated
SETUP	Easy setup (20 min 3 persons)
COLOR	Tent liner: natural white Groundsheet: grey

PACKING

PACKING UNIT (P.U.)	PVC bag
CONTENT P.U.	Tent, frame, groundsheet, accessories and hammer
QTY P.U.	1 piece
P.U. MEASUREMENTS	DIMENSIONS: 240 x 55 x 40 cm WEIGHT: 148 kg VOLUME: 0,528 m ³
QTY PALLET	5 pcs
PALLET MEASUREMENTS	DIMENSIONS: 240 x 100 x 113 cm WEIGHT: 765 kg VOLUME: 2,712 m ³
LOADING	PER 20 FT DC 72 pcs palletized PER 40 FT DC 144 pcs palletized PER 40 FT HC 144 pcs palletized

INDICATED WEIGHTS AND VOLUMES ARE FOR YOUR INFORMATION ONLY AND MAY VARY ACCORDING TO PRODUCT SPECIFICATION.
FOR ALL DIMENSIONS AND WEIGHTS A TOLERANCE OF 3% IS APPLIED

ADD-ONS

Connectability options (gable / lateral / cross connector)	Shade net
Partition set	Inner liner
Ceiling net	