LOW THERMAL FLEECE BLANKET





ICRC/IFRC STANDARD CUSTOMER REFERENCE HSHEBLANPLT1

DESCRIPTION

- » Knitted blanket dry raised on both sides
- » 1 fold fleece layer in 100% virgin polyester
- » Min. 200 gsm max. 400 gsm

MAIN MATERIALS

MATERIAL

100% virgin polyester on dry weight as per ISO 1833
TENSILE STRENGHT

Min. 200 N warp and weft as per ISO 13934-1

TENSILE STRENGHT LOSS

Less than 5% after washing as per ISO 6330

THICKNESS

Min 3,5mm as per ISO 5084 (IKPA on 2000 mm²)

SHRINKAGE

Less than 5% after washing as per ISO 6330

WEIGHT LOSS

Less than 5% after washing as per ISO 6330

TOG Min. 0,15 RCT (= 1,5 TOG)

RESISTANCE TO AIRFLOW Less than 500 L/m²/s as per ISO 9237 under 100 Pa pressure drop

FINISH Whipped seam of min. 10 stitches per 10 cm

ORGANOLEPTIC TEST

No bad smell, not irrating, no dust, PH between 4 and 9, fit for human use and free from

harmful VOC

FLAME RESISTANCE Flame proof as per ISO 12952-3&4
CIGARETTE RESISTANCE Cigarette proof as per ISO 12952-1&2

COLOR Grey shade blanket

DIMENSIONS

LENGHT x WIDTH $150 \times 200 \text{ cm } \pm 1\%$

WEIGHT Min. 200 gsm - max. 400 gsm

LOW THERMAL FLEECE BLANKET

PACKING

PACKING UNIT (P.U.) Compressed bale QTY P.U. 20 pcs per bale

DIMENSIONS: 80 x 53 x 47 cm

P.U. MEASUREMENTS WEIGHT: 22 kg

VOLUME: 0,2 m³

QTY PALLET Up to 8 bales per CRI pallet

DIMENSIONS: 115 x 75 x 115 to 230 cm

WEIGHT: 101 or 190 kg PALLET MEASUREMENTS

VOLUME: 1 or 2 m³

PER 20 FT DC 2920 pcs unpalletized I 2400 pcs palletized LOADING PER 40 FT DC 6000 pcs unpalletized I 4800 pcs palletized

PER 40 FT HC 7200 pcs unpalletized I 4800 pcs palletized

INDICATED WEIGHTS AND VOLUMES ARE FOR YOUR INFORMATION ONLY AND MAY VARY ACCORDING TO PRODUCT SPECIFICATION. FOR ALLDIMENSIONS AND WEIGHTS A TOLERANCE OF 3% IS APPLIED

Specifications & design may be altered without notice due to continuous product development. LAST UPDATED 6/2023

